

Assistant Mason

Sample Paper

Training Provider		Training Center	
Center SPOC		Batch Id	
Center SPOC Contact No		Assessment date	
Candidate Name		Trainer Name	
Candidate Contact No		Trainer Contact No	
Candidate Signature		Trainer Signature	

Q1. What should be checked before erecting a scaffold?

- a) Paint quality
- b) Ground compactness
- c) Wall color
- d) Brick size

Q2. Which component is placed on the ground before scaffold erection?

- a) Trowel
- b) Base plate
- c) Chisel
- d) Float

Q3. Which components are fixed on the working platform for safety?

- a) Tiles
- b) Bricks
- c) Guard rails and toe boards
- d) Mortar pans

Q4. Which tool is used to check level?

- a) Spirit level
- b) Hammer
- c) Chisel
- d) Spade

Q5. Which device is used for transferring levels?

- a) Spirit level
- b) Measuring tape
- c) Paint brush
- d) Bucket

Q6. What should be done after using tools?

- a) Throw away
- b) Clean and maintain
- c) Paint them
- d) Sell them

Q.7 Which tool is used to spread mortar?

- | | |
|-----------|----------------|
| a) Trowel | b) Screwdriver |
| c) Saw | d) File |

Q8. What is used for compaction of concrete?

- | | |
|-------------|-----------|
| a) Vibrator | b) Hammer |
| c) Spade | d) Brush |

Q9. What is mixed with water before anti-termite treatment?

- | | |
|-----------|--------------------------|
| a) Cement | b) Anti-termite solution |
| c) Sand | d) Lime |

Q10. What is carried out over brick soling in PCC flooring?

- | | |
|-------------|---------------------|
| a) Painting | b) Screeding of PCC |
| c) Tiling | d) Polishing |

Q11. What should be removed from the face of the wall?

- | | |
|------------------|--------------|
| a) Excess mortar | b) Paint |
| c) Water | d) Dust only |

Q12. What should be done to bricks before laying?

- | | |
|-------------|------------|
| a) Drying | b) Soaking |
| c) Painting | d) Cutting |

Q13. What is applied before plastering?

- | | |
|------------------|-----------|
| a) Cement slurry | b) Paint |
| c) Oil | d) Grease |

Q14. What is used to fill the gap between wall and door frame?

- | | |
|----------|---------------------|
| a) Sand | b) Non-shrink grout |
| c) Water | d) Gravel |

Q15. Effective teamwork requires?

- | | |
|------------------|--------------|
| a) Communication | b) Silence |
| c) Competition | d) Isolation |

Q16. Deviations from work should be reported to?

- | | |
|-----------------|-----------------------------|
| a) Visitors | b) Co-workers and superiors |
| c) Clients only | d) Nobody |

Q17. Materials and tools should be handed over to interfacing teams?

- | | |
|-----------|------------|
| a) Late | b) Timely |
| c) Weekly | d) Monthly |

Q18. Which type of brick is generally preferred for construction work?

- | | |
|------------------|--------------------------|
| a) Broken bricks | b) Burnt clay bricks |
| c) Mud lumps | d) Hollow plastic blocks |

Q19. Which safety activity is conducted at site?

- | | |
|------------------|---------------|
| a) Tool Box Talk | b) Dance Show |
| c) Picnic | d) Sports Day |

Q20. Construction waste should be deposited into?

- | | |
|-----------------|--------------------------|
| a) Open ground | b) Identified containers |
| c) Water bodies | d) Roadside |