

Mason - Special Finishing

Sample Paper

Training Provider		Training Center	
Center SPOC		Batch Id	
Center SPOC Contact No		Assessment date	
Candidate Name		Trainer Name	
Candidate Contact No		Trainer Contact No	
Candidate Signature		Trainer Signature	

Q1. What is the main purpose of grit wash finishing?

- a) Waterproofing
- b) Decorative surface finish
- c) Structural strengthening
- d) Insulation

Q2. Exposed aggregate plastering is mainly used to:

- a) Increase wall thickness
- b) Improve fire resistance
- c) Provide decorative texture
- d) Reduce cement consumption

Q3. In stone Crete work, the major material used is:

- a) Timber chips
- b) Stone aggregates with cement mortar
- c) PVC sheets
- d) Clay bricks

Q4. Dry stone cladding is fixed using:

- a) Water only
- b) Mechanical anchors and fasteners
- c) Paint
- d) Bitumen

Q5. Wet stone cladding generally uses:

- a) Cement mortar
- b) Adhesive tape
- c) Nails only
- d) Plastic clips

Q6. Cement wash is mainly applied to:

- a) Improve appearance and protection
- b) Increase wall height
- c) Reduce brick size
- d) Strengthen foundation

Q7. POP stands for:

- | | |
|----------------------|---------------------|
| a) Powder of Plaster | b) Plaster of Paris |
| c) Paint on Plaster | d) Polymer of Paint |

Q8. POP punning is done to obtain:

- | | |
|---------------------------|------------------------|
| a) Rough surface | b) Decorative cracks |
| c) Smooth and even finish | d) Waterproof membrane |

Q9. Which tool is commonly used for POP finishing?

- | | |
|------------|------------------|
| a) Trowel | b) Pickaxe |
| c) Crowbar | d) Chisel hammer |

Q10. Moulds in POP work are used for:

- | | |
|-----------------|------------------------------------|
| a) Brick laying | b) Decorative patterns and designs |
| c) Excavation | d) Plumbing work |

Q11. Mosaic flooring is made by embedding:

- | | |
|---------------------------------|-------------------|
| a) Stone chips in cement matrix | b) Bricks in sand |
| c) PVC sheets | d) Wooden planks |

Q12. Terrazzo flooring is known for:

- | | |
|-----------------------|-------------------------------|
| a) Soft surface | b) Decorative polished finish |
| c) Temporary use only | d) Low durability |

Q13. Linoleum flooring is primarily made from:

- | | |
|----------------------|----------------|
| a) Natural materials | b) Pure cement |
| c) Steel sheets | d) Clay tiles |

Q14. Vinyl flooring is preferred because it is:

- | | |
|------------------------|------------------------------------|
| a) Heavy and expensive | b) Waterproof and easy to maintain |
| c) Fragile | d) Non-flexible |

Q15. PVC flooring is widely used due to:

- a) High weight
- b) Easy installation and durability
- c) Poor appearance
- d) Water absorption

Q16. Laminate wood flooring resembles:

- a) Stone flooring
- b) Concrete flooring
- c) Natural wood flooring
- d) Metal flooring

Q17. Before laying floor finishes, the base surface should be:

- a) Dirty
- b) Uneven
- c) Clean and level
- d) Wet and muddy

Q18. The standard thickness of internal plaster is generally:

- a) 5 mm
- b) 50 mm
- c) 100 mm
- d) 12 mm

Q19. Good communication in a team results in:

- a) Misunderstandings
- b) Better coordination
- c) Increased accidents
- d) Poor quality work

Q20. What is the main purpose of special finishing in masonry?

- a) Increase wall thickness
- b) Improve appearance and durability
- c) Reduce cement consumption
- d) Increase wall height